



Wear Studs

- Reduces wear on surfaces exposed to abrasion by forming a barrier between the machinery and the material being moved.
- Consists of applying high-chromium and high-carbon abrasion resistant studs to machinery in close formation.
- Easy to handle, fast application welding gun saves time and labour costs.



FEATURES & BENEFITS

- High abrasion resistance
- Quick & easy application on site
- Permanent protection
- Save on time, power and labour
- Minimise costs and machine down time
- Extend machinery wear life

APPLICATIONS

- Deep Mining Industry
- Open Pit Mines
- Quarries
- Tunneling
- Steelworks
- Ore Preparing

Effectiveness of AVT wear studs in different ground conditions

Ground Condition	Rock-Box-Effect	Impact	Effectiveness
Sand	★★★	Low	★★★
Sand & gravel	★★★	Low	★★★
Gravel & earth, loose	★★★	Low	★★★
Earth, loose	★★★	Low	★★★
Earth & clay	★★★	Low	★★★
Clay & shale loose	★★★	Low	★★★
Shale, tight, blasted	★★	High	★★
Shale & coal, tight, blasted	★★	Moderate	★★
Shale & coal, loose	★★★	Low	★★★
Lignite, sub bituminous coal	★★★	Moderate	★★★
Bituminous coal, blasted	★	Moderate	★★
Anthracite, blasted	★	Moderate	★★
Limestone, blasted	★	High	★
Sandstone & earth, loose	★★★	Moderate	★★
Sandstone, tight, blasted	★	High	★
Phosphate loose or blasted	★★★	Low	★★★
Uranium ore, loose	★★★	Moderate	★★★
Copper ore, loose	★★★	Moderate	★★★
Mineral ores, loose	★★★	Moderate	★★★
Tight areas, blasted	★	High	★
High quartzite, loose or blasted	★	High	★

★ = Poor ★★ = Fair ★★★ = Good

Available in 3 specifications:

Note that all studs include ceramic shield. Other sizes available on request.

Standard

- 16mm with 13mm neck; and
- 20mm with 17mm neck
- Length is 15mm
- Fits standard chucks
- Made for Australian conditions
- Hardness 58-60HRC

Premium

- 16mm with 10mm neck
- Length is 15mm
- Tapered top fits perfectly into the chuck
- Fast loading
- Fits standard chucks
- Hardness 58-60HRC

High Performance

- 16mm with 12mm neck
- Length is 15mm
- Tungsten Carbide insert for higher wear resistance
- Use across 10-20% of total surface area for additional durability
- Insert Hardness is HV1,200

Free call: 1300 55 34 73

Web: www.antec.com.au

Email: anteceng@antec.com.au

NSW (Head Office)
9 Chicago Avenue
Blacktown NSW 2148
P: +61 2 9622 9622
F: +61 2 9622 9199

VICTORIA
90 Turner Street
Port Melbourne VIC 3207
P: +61 3 8645 3222
F: +61 3 9646 7945

QUEENSLAND
5/429 Creek Road
Mt Gravatt QLD 4122
P: +61 7 3420 4099
F: +61 7 3420 4033

SOUTH AUSTRALIA
70 Grand Junction Road
Kilburn SA 5084
P: +61 8 8162 8700
F: +61 8 8162 8704

WESTERN AUSTRALIA
2/17 Baile Road
Canning Vale WA 6155
P: +61 8 6350 9600
F: +61 8 6350 9601